| Question | Answer 1 | Answer 2 | Answer 3 | Answer 4 | CorrectOption |
|--|--|--|---|---|---------------|
| package contains all the classes and methods required for even handling in Java? | a. java.applet | java.awt | java.event | java.awt.event | Answer4 |
| AWT stands for? | Applet Windowing Toolkit | Abstract Windowing Toolkit | Absolute Windowing Toolkit | Alert Window Toolkit | Answer2 |
| Which is the container that doesn't contain title bar and MenuBars but it can | | | | | |
| have other components like button, textfield etc? | Window | Frame | Panel | Container | Answer3 |
| Which package provides many components for swing? | java.swing.* | java.awt.graphics.* | javax.swing.* | java.applet.* | Answer3 |
| All swing components are ? | heavyweight | lightweight | AWT | Applet | Answer2 |
| Which method is used to set the close operation in swing? | setDefaultCloseOperation(J Frame.EXIT_ON_CLOSE) | SetDefaultCloseOperatio n(jFrame.EXIT_ON_CLOS E) | setDefaultCloseOperation() | setClose() | Answer1 |
| Default value of setDefaultCloseOperation() method is | DO_NOTHING_ON_CLOSE | HIDE_ON_CLOSE | DISPOSE_ON_CLOSE | EXIT_ON_CLOSE | Answer2 |
| gets the number of items in the JComboBox? f a query is to be executed multiple times, which of the following should be | getItem() | getSelectedItem() | getItemCount() | getCount() | Answer3 |
| ised? | Statement | PreparedStatement | CallableStatement | CallStatement | Answer2 |
| n a driver, a pure Java-based driver communicates directly with the endor's database. | Type 4 | Type 1 | Type 2 | Type 3 | Answer1 |
| Vhich of the following is the first step to create a servlet? | Loading Servlet | Create Instance of Servlet | Call the Servlets init() Method | Call the Servlets service () Method | Answer1 |
| he method allows a servlet to initialize itself before the first request sprocessed. | service() | init() | destroy() | getServletConfig() | Answer2 |
| Vhich of the following package contains servlet classes? | javax.servlet | javax.servlet.http | Both javax.servlet and javax.servlet.http | Neither javax.servlet nor javax.servlet.http | Answer3 |
| Which of the following is the correct order of servlet life cycle phase methods? | <pre>init(), execute(), delete()</pre> | init(), service(), delete() | init(), execute(), destroy() | init(), service(), destroy() | Answer4 |
| IttpServletResponse extends interface which provides functionality a sending response. | ServletRequest | ServletResponse | ServletConfig | ServletContext | Answer2 |
| is a small piece of information that is persisted between the nultiple client requests. | cookie | Hidden Form Field | HttpSession | Session | Answer1 |
| is valid for single session only and it is removed each time when ser closes the browser. | Persistent cookie | Non-persistent cookie | Both Persistent and Non- persistent cookie | Neither Persistent nor Non-persistent cookie | Answer2 |
| is valid for multiple session . It is not removed each time when ser closes the browser. It is removed only if user logout or signout. | Both Persistent and Non- persistent cookie | Neither Persistent nor Non-persistent cookie | Persistent cookie | Non-persistent cookie | Answer3 |
| class provides the functionality of using cookies. | javax.Cookie | javax.http.Cookie | javax.servlet.Cookie | javax.servlet.http.Cooki e | Answer4 |
| n case of Hidden Form Field a hidden is used for maintaining the state of an user. | textArea | PasswordField | textfield | formField | Answer3 |

| defines file to be included. | include directive | taglib directive | page directive | import directive | Answer1 |
|--|---------------------------------|--|---|--|---------|
| Which of the following is known as JSP Dirctive tag . A)<%= %> B) <%@ %> C)<%! %> D) <%%> | А | В | С | D | Answer2 |
| Which of these is correct about the JSON standard? | It is an open standard | It is privately developed | It requires a license to use | It is protected key | Answer1 |
| Which of these data interchange formats has seen a decline in usage in favor of JSON? | ASCII | Plain-text | SQL | XML | Answer4 |
| What function will convert a JavaScript object to a JSON string? | JSON.text() | JSON.serialize() | JSON.toString() | JSON.stringify() | Answer4 |
| JSON stands for ? | JavaSource Object Network | JavaScript Object Network | JavaScript Object Notation | Jason Script Object Notation | Answer3 |
| are used for transferring data between server and client. | JSON objects | XML | Neither XML nor JSON objects | Both XML and JSON objects | Answer4 |
| In what situation would you want to use XML over JSON? | When JSON is not offered. | When you need to use tags to structure your content. | You need message validation or you're using XSLT. | Never, JSON is worlds better. | Answer3 |
| Can you use a double quote inside a JSON string? | Yes, if you use the ascii code. | Yes, you can use it without any special treatment | Yes, if it is escaped like (\") | No, you should use single quotes | Answer3 |
| Which of the following method of value stack is used to get the object on the top of the stack without changing the stack? | add() | push() | peek() | pop() | Answer3 |
| Which of the following method of value stack is used to set an object on the stack with the given key so it is retrievable by findValue(key,)? | setObject(String key, Object o) | set(String key, Object o) | set Default Type (Class default Type) | setValue(String expr, Object value) | Answer2 |